



FIRE PROTECTION for GAS, PROPANE and ELECTRIC RANGES To conform to Section 8.16.22 - 2006 B.C. BUILDING CODE

STAIRS, GUARDS and HANDRAILS to conform to Section 9.8 - 2006 B.C. Building Code

Tampered Glass or Glass Block required at all windows & shower enclosures. Waterproof wall flash to 432mm (17") above the rim of tub/shower and 1.2m (48") for those equipped with shower & 1.8m (77") for shower stalls.

SMOKE ALARMS CANULC 5531 shall be installed on every floor level within 5m (16.4ft) of bedrooms and 15m (49.2ft) of all other areas of the dwelling 9.10.16.2-2006 B.C.B.C.

CARBON MONOXIDE DETECTORS CSA 6.19 shall be installed in a dwelling which contains a fuel burning appliance and/or storage garage. Placed in each bedroom within 5m (16.4ft) outside of each bedroom door. Have no disconnect switch between the over current device and the alarm and be equipped with an integral alarm which satisfies the auditory requirements of CSA 6.19 Residential Carbon Monoxide Alarming Devices. Mechanically fixed at a height recommended by the manufacturer.

UPPER FLOOR AREA: 1,347 SQ.FT.

# UPPER FLOOR PLAN

SCALE: 1/4" = 1'-0"



PROJECT NAME: AMMIRATI RESIDENCE



1433 ST. PAUL STREET, KELWYN B.C. V3Y 2K6  
Tel: 604-750-8143 Fax: 604-750-7400  
www.nesbittoriginals.com

SHEET TITLE: UPPER FLOOR PLAN

ISSUED FOR: CONSTRUCTION WORKING DRAWINGS

DATE: YYYY-MM-DD 2009-06-30

SCALE: 1/4" = 1'-0"

LOT C, DL 210, S.D.Y.D., PLAN 29459.

4